

HARVY®
200
SERIES

Features & Benefits



HARVY200 - Manual Framed Model

- Portal Framed, Over-the-Row (OTR) solution
- Patented Soft-Catch System: with bush-sealing brushes and catching sheets to ensure berries land softly, preventing bruising and reducing ground loss.
- For use in open fields.



HARVY200S - Split Portal Model


- No portal frame, split model of HARVY200.
- For use in fields with screens/netting or permanent roof construction with upright supports, and ideal for tunnels.



HARVY200E - Electric Drive Framed Model

- Redesigned frame and roof structure of HARVY200.
- Electric drive offers constant, controlled forward movement, reducing physical exertion
- For use in tunnels, environments with limited height or space, and narrow fields with longer rows and rough, wet, or uneven terrain.

Harvest Speed	Dependent on labor team performance.
Daily Yield	Up to 1,500 kg in a 10-hour workday Up to 3,300 lb in a 10-hour workday
Ground Loss	<5% loss discarded on the ground
Picking Cost	> 20 cents/lb >.18 eu/kg
Energy Source	Manually propelled (HARVY200, HARVY200S) Electric powered (HARVY200E)
Soft-Catch System (Patented)	Brushes gently seal bushes to maximize the collection of fruit and reduce ground loss. Canvas catch sheets ensure berries land softly to prevent bruising and maintain fruit quality.



Dimensions (HARVY200)

Length:	3300 mm 130 in
Width:	2150-3000 mm 84.65-118.22 in
Height	2160 mm 85.04 in

Weight

195 kg | 430 lb